


MTP235 CS2 Primary Cleaner

Installation, Operation and Maintenance Manual



Purchase Date: _____

Purchased From: _____

Installation Date: _____

This information will be helpful for any future inquiries or questions
about belt cleaner replacement parts, specifications or troubleshooting.

Contents

Section 1 – Important Information..... 4

1.1 General Introduction..... 4

1.2 User Benefits 5

1.3 Service Option 5

Section 2 – Safety Considerations and Precautions..... 5

2.1 Stationary Conveyors..... 5

2.2 Operating Conveyors..... 7

Section 3 – Pre-installation Checks and Verifications..... 8

3.1 Checklist..... 8

Section 4 – Installation Instructions 9

4.1 MTP235 CS1 Cleaner – Chute Mounting 10

4.2 Cleaner X, Y Locations Modifications (If required)..... 11

4.3 Installing MTP235 CS2 13

Section 5 - Trouble shooting.....16

Section 6 - Maintenance17

6.1 New Installation Inspection 17

6.2 Visually inspect belt cleaner on a regular basis 17

6.3 Routine Physical Inspection/adjustments..... 18

6.4 Spare Parts and Specifications 18

Section 7 - MTP235 CS1 Specifications:18

Section 1 – Important Information

1.1 General Introduction

This manual is intended to help you understand how this product operates and to assist you in achieving maximum efficiency throughout its service life. For the product to function safely and effectively, it is important that the information and guidelines provided are fully understood and followed. Within this manual you will find safety precautions, installation instructions, maintenance procedures, and troubleshooting guidance. If you encounter questions or issues not addressed here, please visit our website or contact our Customer Service Department.

Please review this manual carefully and ensure it is provided to anyone who will be directly involved in the installation, operation, or maintenance of this cleaner. Although the installation and servicing procedures have been designed to be as straightforward as possible, proper installation along with routine inspections and maintenance are still necessary to keep the cleaner operating at peak performance.

Customer Service:

Australia/South-East Asia

MATO Australia Pty Ltd.
Tel: +61 1300 850 795
maus@mato.com.au

United Kingdom

MATO Industries Ltd
Tel: +44 (0) 1254 3876 38
info@mato.co.uk

South Africa

MATO Products Pty Ltd.
Tel: +27 (0) 1192 3602 4
matosales@multotec.co.za

China

MATO Industrial Technology
Tel: +86 5374 5337 99
info@mato.com.cn

North America

MATO Corp
Tel: +1(1) 3042 551280
info@mato-usa.com

South America

MATO LATAM
Tel: +57 3173 6207 51
csouto@mato.latam.com

Germany - Europe

MATO GmbH & Co Kg
Tel: +49 (0) 6108 906 0
beltlacing@mato.de

Visit **www.mato.com.au** for other MATO locations and products.

MAN519 - Revision – 01

www.mato.com.au

Page | 4

©2026 MATO Australia Pty Limited

1.2 User Benefits

Proper installation along with consistent maintenance can deliver the following advantages for your operation:

- Decreased conveyor downtime
- Reduced labour hours
- Lower overall maintenance budget requirements
- Extended service life for the belt cleaner and other conveyor components

1.3 Service Option

The MTP235 Cleaner is engineered for straightforward installation and servicing by your onsite personnel. If you would rather have full turn-key factory service, please reach out to your local MATO Field Representative.

Section 2 – Safety Considerations and Precautions

Before installing or operating the MTP235 Cleaner, it is essential to review and understand the safety information provided. Various set-ups, maintenance, operational tasks involve contact with stationary and operating conveyors. Each situation requires adherence to its specific safety protocol.

2.1 Stationary Conveyors

The following tasks are carried out when the conveyor is stationary and isolated:

- Installation
- Blade replacement
- Repairs
- Tension adjustments
- Cleaning

DANGER

It is essential that all Lockout/Tagout regulations are followed before performing any of the above activities. Not applying Lockout/Tagout procedures exposes personnel to unexpected movement of the conveyor belt, which can cause uncontrolled action of the belt cleaner. Serious injury or fatal consequences may result.

Before working:

- Lockout/Tagout the conveyor power source
- Follow site regulations/instructions for belt maintenance
- ensure work site is safe to carry out work

WARNING

Use Personal Protective Equipment (PPE):

(as per site requirements)

- Safety eyewear
- Hardhats
- Safety footwear
- Safety gloves

Close quarters, springs and heavy components create a worksite that compromises a worker's eyes, feet and skull. PPE must be worn to control the foreseeable hazards associated with conveyor belt cleaners. Serious injuries can be avoided.

2.2 Operating Conveyors

There are two routine tasks that must be performed while the conveyor is running:

- Inspection of the cleaning performance
- Dynamic troubleshooting

DANGER

Every belt cleaner presents an in-running nip hazard. Never touch or interfere with a cleaner while it is in operation. Hazards associated with an operating cleaner can result in immediate amputation or entrapment. Do not attempt to make any adjustments while the cleaner is running.

WARNING

Unexpected belt tears or projections may catch on the cleaner, causing sudden and forceful movement of the cleaner assembly. Loose or flailing components can lead to severe injury or death.

WARNING

Belt cleaners can also become projectile hazards. Maintain as much distance from the cleaner as reasonably possible and always wear appropriate PPE. Flying debris can cause serious harm.

Section 3 – Pre-installation Checks and Verifications

3.1 Checklist

- Verify that the cleaner size matches the belt width
- Inspect the belt cleaner carton to confirm all required parts are present
- Review the “Tools Needed” list at the top of the installation instructions
- Inspect the conveyor site:
 - Ensure the conveyor being serviced, along with any upstream/downstream conveyors, is fully isolated in accordance with regulatory and site procedures
 - Determine whether the cleaner will be installed on a chute
 - Identify if the installation is on an open head pulley that will require mounting structure
 - Check for any obstructions that may necessitate adjustments to the cleaner’s location
 - Carry out a complete risk assessment and safe method statement as required by site standards for the work area, and prepare a job plan based on the instructions provided here

Note:

That the installation instructions provided should be regarded as typical guidelines and recommendations. These installation instructions may not fully reflect site conditions and/or safety requirements.


Section 4 – Installation Instructions

MTP235 CS2 Cleaner

MTP235 CS2 - MOUNTING

Tools required:

- Rule
- Tape measure
- Marking pen
- Level
- 15/16" (24mm) spanner
- Pinch bar



***Physically lock out and tag the conveyor at the power source
before you begin cleaner installation.***


4.1 MTP235 CS2 Cleaner – Chute Mounting

Installation specifications and instructions are based on the assumption that the conveyor is in its working position (angle). If the conveyor angle will be different, the cleaner mounting brackets should be installed per the final position, parallel to conveyor structure.

1. Locating correct shaft position. Measure and determine Dimension A. Find Dimension A on the Shaft Location Chart (refer to fig.1) and determine Dimensions X, Y and C.
2. Measure out from the center of pulley shaft parallel with ground level, mark out 'X' dimension. From 'X' dimension, draw a line down perpendicular with ground line, then measure and mark out dimension 'Y' (refer to fig.2). This indicates the location of the center of the cleaner shaft. Measure and mark out both sides of pulley.

Pulley Diameter = _____ mm; X = _____ mm; Y = _____ mm; C = _____

Using the correct X and Y coordinates will position the cleaner at 15° below the center line of the pulley (center line parallel with ground level) on the head pulley.



Note:

If modifications are required to 'X' and 'Y' dimensions due to obstruction in existing structure, please refer to page 11.

4.2 Cleaner X, Y Locations Modifications (If required)

In certain installations, it may be required to adjust the location of a primary cleaner shaft due to structural obstructions that prevent installation at the recommended position. The shaft location can be relocated without affecting cleaner performance, provided the critical "C" dimension is maintained.

1. Determine Required Modification

Mark out the existing X and Y dimensions as per shaft location chart (fig.1 pg. 10). Identify the amount of relocation required to provide sufficient clearance for the shaft and tensioning assembly. For an example if we determine the 'Y' dimension needs to be lowered by 25mm to clear all structure, we now have 2 dimensions out of 3 required to locate shaft. ('C' and 'Y' are known and 'X' is to be calculated).


2. Calculate the New X Dimension

From center of pulley draw a vertical line down and horizontal line across (fig. 2). Measure down from the intersection the newly determined 'Y' dimension and mark (fig. 3). From this new Y reference point, measure diagonally across toward the horizontal line using the fixed 'C' dimension, mark where it intersects the horizontal line (fig. 4). Measure from the original intersection point along the horizontal line to this new intersection. This measurement is the revised X dimension (fig. 5).

Example


If we use a pulley size of 250 ('A') 'X' = 118mm, 'Y' = 180mm, 'C' = 215mm and we determine that 'Y' needs to be lowered by 25mm. we know 'Y' = 205mm, 'C' = 215mm and 'X' = unknown

By following these steps, in this example we can determine that 'X' = 65mm



3. Mark out and trace mounting template. Using the mounting template provided (as shown in fig. 2) in the instruction packet, position the shaft access hole on the chute aligned with 'X' and 'Y' coordinates. Trace the shaft cut-out and mounting slotted holes. Repeat on opposite side of pulley.

NOTE: Hole cut outs are slotted for later adjustment if needed.



Example of locating mounting plate template parallel with belt feed line

4.3 Installing MTP235 CS2

- 1- Bolt the mounting brackets along with torque arm to the drilled-out holes on chute or conveyor structure using supplied fasteners.
(fig 7)




fig 7

- 2- Insert shaft through mounting blocks to opposite side.
(fig 8)




fig 8

- 3- Position shaft center to pulley loosely and install pivot bushes.
(fig 9)




fig 9

- 4- Install tensioning assembly.
Torsion arm will fit snug against pivot block,
bolts on the torsion arm, are to remain loose.
Confirm shaft center to pulley
(fig 10)




fig 10

- 5- Install blade and retaining pins to shaft, confirm shaft is center to pulley.
(fig 11, fig 12, fig 13)




fig 11




fig 12




fig 13

- 6- Rotate shaft up to have blade point rest against pulley. Tighten torque clamp bolts to shaft to hold shaft in correct Position. Confirm that heel gap of blade is 3-5mm
(fig 14, fig15)




fig 14




fig 15

7- Setting blade tension

Once tensioning assembly is installed to cleaner use the spring tensioning chart (fig.16) to set blade tension to belt.

(note measurement to be taken of spring compression, do not include bushings)

MTP235 CS2 SPRING TENISONING CHART

BLADE WIDTH	SILVER SPRING	YELLOW SPRING
mm	mm	mm
450	146	
600	144	
650	142	
750	140	
850	138	
900	136	
1050	134	
1250		135
1350		133
1450		131
1650		129
1850		127
1950		125
2250		123




fig.16

8- Test run conveyor and inspect cleaner performance.

Run conveyor for 15minutes to determine if there is excess vibration and efficiency of cleaner.

Section 5 - Trouble shooting

Problem	Possible Cause	Possible Solution
Poor cleaning performance	Cleaner under-tensioned	Adjust to correct tensions – see spring compression chart
	Cleaner over- tensioned	
	Cleaner blade worn or damaged	Verify 'X, Y and C' dimensions, relocate to correct dimensions
		Replace Blade
Rapid blade wear	Tension on cleaner too high/low	Adjust to correct tension – see spring compression chart
	Cleaner not located correctly	Check cleaner location for correct dimensions
	Blade attack angle incorrect	Verify blade heel gap 3-5mm, adjust 'X, Y' dimensions, adjust to create correct heel gap
	Material too abrasive for the blade	Option: switch to cleaner with tungsten blades or replace blade with greater PU
		Install spray bar
Center wear on blade (smile effect)	Mechanical splice damaging blade	Repair, skive or replace splice
	Blade wider than material path	Replace blade width to match material path
Unusual wear or damage to blade	Tension on cleaner too high/low	Adjust to correct tensions – see spring compression chart
	Mechanical splice damaging the blade	Repair, skive or replace splice
	Belt damaged or ripped	Repair or replace belt
	Cleaner not correctly located	Verify 'X, Y and C' dimensions, relocate to correct dimensions
Vibration or noise	Damage to pulley or pulley lagging	Repair or replace pulley
	Cleaner not located correctly	Verify blade heel gap 3-5mm, adjust 'X, Y and C' dimensions, relocate to correct dimensions
	Blade attack angle incorrect	
	Cleaner running on empty belt	Use spray bar when belt is empty
		Belt is empty or dry
	Cleaner tension too high/low	Adjust to correct tension or slight adjust to diminish
	Cleaner not square to head pulley	Verify 'X, Y and C' dimensions, relocate to correct dimensions
Cleaner being pushed away from pulley	Material build up in chute	Clean build up off cleaner and chute
	Cleaner locking bolts not secure	Check and tighten all bolts and nuts
	Cleaner tension not set correctly	Ensure correct tension/increase tension slightly
	Stocky material is overburdening	Increase tension; replace with cleaner with metal tips; replace with larger cleaner
	Cleaner not set up correctly	Confirm location dimensions are equal on both sides

Section 6 - Maintenance

MATO belt cleaners are built to function with minimal attention; some servicing is still necessary to keep performance at a high level. Once the cleaner has been installed, a routine maintenance schedule should be established. Following such a schedule helps ensure the cleaner continues to run at peak efficiency and allows potential issues to be detected and resolved before the cleaner fails.

All safety requirements for inspecting the equipment—whether stationary or in operation—must be followed. The MTP235 cleaner operates at the conveyor's discharge end and remains in direct contact with the moving belt. While the belt is in motion, only visual checks are permitted. Any service activities must be carried out only when the conveyor is shut down, and proper lockout/tagout procedures must be strictly observed.

6.1 New Installation Inspection

After the cleaner has been operating for several days, carry out a visual review to confirm that it is functioning correctly. Make any required adjustments at this time.

6.2 Visually inspect belt cleaner on a regular basis

A periodic visual check of both the cleaner and the belt can indicate:

- Whether the spring length matches the specification needed for proper tensioning
- Whether the belt surface appears clean or shows sections with material build up
- Whether the blade shows excessive wear and should be replaced
- Whether the blade or any other cleaner components show signs of damage
- Whether fugitive material has accumulated on the cleaner or within the transfer area
- Whether there is any belt cover damage
- Whether the cleaner is vibrating or bouncing on the belt
- If a snub pulley is installed, whether there is material build up on the pulley

If any of these conditions are present, decide when the conveyor can be safely shut down to perform cleaner maintenance.

6.3 Routine Physical Inspection/adjustments

With the conveyor fully stopped and properly locked and tagged out, conduct a hands-on inspection of the cleaner, including the following tasks:

- Remove any material build up from the cleaner blade and shaft
- Examine the blade closely for wear or damage and replace it if necessary
- Inspect both blade pins and retaining clips to confirm correct installation and condition; replace if required
- Verify that the blade maintains full contact with the belt
- Check the cleaner shaft for any signs of damage
- Inspect all fasteners for tightness and wear; tighten or replace where needed
- Replace any cleaner components that are worn or damaged
- Check the blade-to-belt tension and adjust it if needed using the chart on the cleaner or the chart on Page 15
- After all maintenance steps are completed, run the conveyor to confirm the cleaner is functioning as expected

6.4 Spare Parts and Specifications

The MTP235 CS2 cleaner – the Mato Drop on Primary cleaner is the simplest primary cleaner available on the market, with its easy tension spring application for constant tensioning and reduced adjustability. Quick and easy blade replacement by removing the blade locking pins is simple. The MTP235 range of polyurethane primary cleaners are manufactured with a unique self-lubricating blade to reduce friction and blade wear.

Section 7 - MTP235 CS2 Specifications:

- Blade widths available in minus 50mm and 200mm to belt width
- MTP235 cleaners are supplied with a single tensioned end assembly
- Belt speeds up to 3.5m/s
- Suits pulleys diameters from 250mm – 900mm
- Suitable for reversing conveyors
- Blade material 85A shore
- Temperature rated -35°C – 82°C
- Suitable for conveyors fitted with mechanical fasteners

[illegible]

C:\mas\va\miso\va\miso1-Production\NEW FOLDER STRUCTURE\PRIMARY CLEANERS\MTP - PRIMARY CLEANERS\CS2 - END ASSEMBLIES\MTP235-CS2-MSTR

8			7	
BELT WIDTH	BLADE QTY.	CLEANED WIDTH	60 DIAMETER SHAFT LIGHT DUTY SPRING KIT	76 DIAMETER SHAFT MEDIUM DUTY SPRING KIT
450	2	300	81 012 83	81 014 84
600	3	450		
750	4	600		
900	5	750		
1050	6	900		
1200	7	1050	81 012 84	81 014 82
1400	8	1200		
1500	9	1350		
1600	10	1500		
1800	11	1650		
2000	12	1800		


BLADE CHART AND SPRING CHART

60 DIAMETER SHAFT CLEANER RANGE - LIGHT DUTY

ITEM NO.	DESCRIPTION	QTY.	PART NO.
1	MTP-60-450	1	81 022 01
	MTP-60-600		81 022 02
	MTP-60-750		81 022 03
	MTP-60-900		81 022 04
	MTP-60-1050		81 022 05
	MTP-60-1200		81 022 06
	MTP-60-1400		81 022 07
	MTP-60-1500		81 022 08
	MTP-60-1600		81 022 09
	MTP-60-1800		81 022 10
	MTP-60-2000		81 022 11
2A	MDP185 CS2 RED SPRING - KIT	2	81 012 83
2B	MDP185 CS2 SILVER SPRING - KIT	2	81 012 84
3A	MTP235 P1 150mm BLADE (FRAS)	SEE CHART	81 110 00 23
3B	MTP235 P2 150mm BLADE (SELF LUBRICATING)		81 110 00 29
4	END STOP, ASSY. - MTP	2	82 200 00 25
5	TORSION ARM 60.3	2	81 311 12
6	MDP185 - 60.3 PIVOT BUSH (BLACK)	2	81 011 51
7	MDP185-CS2 MOUNTING KIT	2	81 012 71
8	MDP185-CS2 TORQUE ARM KIT	2	81 012 72

76 DIAMETER SHAFT CLEANER RANGE - MEDIUM DUTY

ITEM NO.	DESCRIPTION	QTY.	PART NO.
1	MTP-76-450	1	81 024 01
	MTP-76-600		81 024 02
	MTP-76-750		81 024 03
	MTP-76-900		81 024 04
	MTP-76-1050		81 024 05
	MTP-76-1200		81 024 06
	MTP-76-1400		81 024 07
	MTP-76-1500		81 024 08
	MTP-76-1600		81 024 09
	MTP-76-1800		81 024 10
	MTP-76-2000		81 024 11
2A	MDP185HD/235 CS2 SILVER SPRING - KIT	2	81 014 84
2B	MDP185HD/235 CS2 YELLOW SPRING - KIT	2	81 014 82
3A	MTP235 P1 150mm BLADE (FRAS)	SEE CHART	81 110 00 23
3B	MTP235 P2 150mm BLADE (SELF LUBRICATING)		81 110 00 29
4	END STOP, ASSY. - MTP	2	82 200 00 25
5	TORSION ARM 76.1	2	81 311 13
6	MDP185HD-235-76.1 PIVOT BUSH (BLACK)	2	81 011 49
7	MDP185HD&235-CS2 MOUNTING KIT	2	81 014 71
8	MDP185HD/235-CS2 TORQUE ARM KIT	2	81 014 72



					MACHINING AND FABRICATION TOLERANCES UNO: (ALL DIMENSIONS IN mm) DIMENSIONAL TOLERANCE: PIPE STRAIGHTNESS X.X ±1.0 <1000 ±3.0 X.XX ±0.5 <2000 ±6.0 X.XXX ±0.1 <3000 ±9.0 X.XXXX ±0.01 ANGLE: X.X ±1.0° X.XX ±0.5° THERMAL CUTTING: ±1.0 WELDMENTS: ±2.0 CASTINGS: REFER TO CASTING NOTES MACHINING 'ROUGH' TO ISO 2768-vL MACHINING STD. TO ISO 2768-mK POLYURETHANE: ±2.0 WELD SYMBOLS: IN ACCORDANCE TO ISO 2553 MACHINED SURFACES UNO: TO BE 12.5 / WHERE INDICATED 'ROUGH' 3.2 / WHERE NOT INDICATED		MATERIAL: N/A	DRAWN BY JS	DESCRIPTION: MTP235 - CS2 - SPARE PARTS BREAKDOWN		PROFILE CUT ITEMS: TO BE CUT FROM SUPPLIED DXF CAD FILE WHERE APPLICABLE ADDITIONAL DIMENSIONS CAN BE PROVIDED ON REQUEST DO NOT SCALE IF IN DOUBT © COPYRIGHT, ALL RIGHTS RESERVED THIS DRAWING IS STRICTLY CONFIDENTIAL AND MUST NOT BE COPIED, REPRODUCED OR ADAPTED, NOR MAY ARTICLES BE MANUFACTURED IN ACCORDANCE WITH THE DRAWING WITHOUT PRIOR WRITTEN PERMISSION OF MATO AUSTRALIA PTY LTD.		mato MATO AUSTRALIA PTY LTD (INCORPORATED IN NSW) ABN 62 050 057 726 39 BORVILLE AVE THORNTON NSW 2322 PH: 1300 850 795 FAX: (02)4936 1388		
REVISIONS					FINISH: N/A	CHECKED DG 16/07/26	APPROVED DG 16/07/26	PART NO. N/A							
REV.	DESCRIPTION	BY	APR'VD	DATE	COLOUR: N/A	MFG'D: INTERNAL	CREATED 15/12/2025			MASS: N/A	3RD ANGLE PROJECTION	DRAWING NO. N/A	PG. SIZE A3	SHEET 1 / 1	REV A
A	ISSUED FOR INFORMATION	JS	DG	16/07/26			SCALE DO NOT SCALE								